

MATERIAL SAFETY DATA SHEET

MSDS Name: SF-400 SUBFLOOR & CONSTRUCTION ADHESIVE
MSDS Number: 40029
Version Number: 2
MSDS Date: SEP-09-2002
Page Number: 1

SECTION I - PRODUCT AND COMPANY INFORMATION

Product Name: SF-400 SUBFLOOR & CONSTRUCTION ADHESIVE
HMIS Hazard Rating: Health: 1 Fire: 3 Reactivity: 0 PPE: B

Company Identification: OSI SEALANTS, INC. a Subsidiary
of Sovereign Specialty Chems.
7405 PRODUCTION DRIVE
MENTOR OH 44060

Information phone/Fax: (440) 255-8900 (440) 974-8358
Emergency Phone (24 hour) CHEMTREC
(800) 424-9300
Chemtrec (outside-USA) (703) 527-3887

Product Class: ADHESIVE
Trade Name: PRO-SERIES
Product Code: 40011, 40029

SECTION II - INGREDIENT AND HAZARD INFORMATION

Hazardous Ingredient Name	CAS Number	Percent	TSCA
Light Aliphatic Naphtha	64742-89-8	10 - 15	Y
Toluene	108-88-3	5 - 10	Y
n-Hexane	110-54-3	5 - 10	Y
Ethanol	64-17-5	< 5.0	Y

Ingredient Notes:
Remaining ingredients are not considered OSHA hazardous.

SECTION III - PHYSICAL AND CHEMICAL PROPERTIES

Form: Mastic adhesive
Appearance/Color: Tan
Odor: Slight, hydrocarbon

MATERIAL SAFETY DATA SHEET

MSDS Name: SF-400 SUBFLOOR & CONSTRUCTION ADHESIVE

MSDS Number: 40029

Version Number 2

MSDS Date: SEP-09-2002

Page Number: 2

Solubility (in water): Insol. in water
pH Value, +/- .3: Not Applicable
Boiling Range: 160.°F - 230.°F (71.11°C - 110.°C)
Vapor Pressure (mmHg): 155. @ 68.°F (20.°C)
Evaporation Rate: 4.8 times Faster than n-Butyl Acetate

Vapor Density: Heavier than air

% Volatile, Weight approx. 32.%
% Volatile, Volume 45.%
Specific Gravity: 1.09283
VOC (less H2O or exempt) 370 g/l (32wt%)

NOTE:

*BOIL RANGE, EVAP RATE, VAPOR DENSITY AND PRESSURE FOR SOLVENT ONLY!

SECTION IV - FIRE FIGHTING MEASURES (Flash,UEL,LEL for solvent only)

Flammability Class I B
Flash Range: 0.°F - 60.°F (-17.78°C - 15.56°C)
Tag Closed Cup
Explosive Range (LEL/UEL): 1.%
6.5%

EXTINGUISHING MEDIA:

Carbon Dioxide---Dry Chemical---Foam
Use water fog to cool material in vicinity of fire.

SPECIAL FIRE-FIGHTING PROCEDURES:

Use self-contained breathing apparatus with full facepiece
operated in pressure demand with full protective equipment.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

Any closed container may rupture when exposed to extreme heat.
Solvent vapors are heavier than air and travel along the ground.
Vapors given off are flammable and may be ignited in air explosively.

SECTION V - HEALTH HAZARD DATA

ROUTES OF ENTRY:

ENTRY THROUGH... Inhalation and skin most likely

CARCINOGENICITY...

NTP? N/E | IARC Monographs? N/E | OSHA? NO

MATERIAL SAFETY DATA SHEET

MSDS Name: SF-400 SUBFLOOR & CONSTRUCTION ADHESIVE
MSDS Number: 40029
Version Number: 2
MSDS Date: SEP-09-2002
Page Number: 3

EFFECTS OF OVEREXPOSURE

Eyes: Can cause irritation, redness, tearing and blurred vision.
Skin: Prolonged or repeated contact can cause moderate irritation, drying of the skin, and dermatitis.
Inhalation: Excessive inhalation of vapors can cause respiratory irritation, headache, drowsiness and fatigue. High concentrations of vapors are anesthetic and may cause central nervous system effects such as dizziness.
Ingestion: Can cause gastrointestinal irritation, nausea, vomiting and diarrhea.

FIRST AID MEASURES

Eyes: Flush eyes gently with water for at least 15 minutes lifting eyelids occasionally; get prompt medical attention
Skin: Wash thoroughly with soap and water; apply a mild skin cream. Remove contaminated clothing.
Inhalation: Move affected person to fresh air; if breathing is difficult, administer oxygen; if breathing has stopped, give artificial respiration. Get medical attention.
Ingestion: DO NOT INDUCE VOMITING! Get immediate medical attention.

CHRONIC HAZARDS

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain, nervous system, liver or kidney damage or may cause cardiac arrhythmia. INTENTIONAL misuse of this product by deliberately inhaling its vapors may be harmful or fatal.
N-Hexane can cause peripheral neuropathy (arm and leg damage) and central nervous system damage. Prolonged and repeated exposure has been suggested as a cause of the following effects in lab animals: liver and reproductive abnormalities, kidney, spleen, lung or eye damage. May aggravate pre-existing disorders of these organs in humans. May be harmful if absorbed through skin.
Repeated overexposure to Toluene may cause liver damage.
Toluene has been found to cause Kidney, Lung and Spleen damage in laboratory animals.

SECTION VI - STABILITY AND REACTIVITY

Stability: This product is stable
Hazardous Polymerization: Hazardous polymerization will not occur

INCOMPATIBILITY:

Keep away from strong oxidizing agents.

CONDITIONS TO AVOID:

MATERIAL SAFETY DATA SHEET

MSDS Name: SF-400 SUBFLOOR & CONSTRUCTION ADHESIVE

MSDS Number: 40029

Version Number 2

MSDS Date: SEP-09-2002

Page Number: 4

Keep away from heat, spark, open flames and any ignition source.

HAZARDOUS DECOMPOSITION PRODUCTS:

Will produce fumes and smoke containing carbon monoxide and dioxide under fire conditions.

SECTION VII - ACCIDENTAL RELEASE AND DISPOSAL MEASURES:

STEPS TO BE TAKEN IN CASE OF SPILL:

Eliminate all ignition sources. Ventilate confined areas. (Open windows and doors). Wear appropriate protective clothing. Cover with absorbent. Scoop into sealable safety container.

WASTE DISPOSAL METHOD:

Dispose of following local, state, and federal regulations.

SECTION VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits

	ACGIH TLV	ACGIH TLV-C	ACGIH STEL	OSHA STEL	OSHA PEL
Light Aliphatic Naphtha					
	400.00 PPM	N/est	N/est	1000.00 PPM	500.00 PPM
Toluene					
	100.00 PPM	N/est	150.00 PPM	150.00 PPM	150.00 PPM
n-Hexane					
	50.00 PPM	N/est	N/est	N/est	50.00 PPM
Ethanol					
	1000.00 PPM	N/est	N/est	N/est	1000.00 PPM

RESPIRATORY PROTECTION:

If TLV of the product is exceeded, a NIOSH/MSHA jointly approved air supply respirator is advised in the absence of proper ventilation. OSHA regulations also permit the use of other types of NIOSH/MSHA respirators under specified conditions. (See your safety equipment supplier for more information)

VENTILATION:

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV. Ventilate during application and curing of this product.

MATERIAL SAFETY DATA SHEET

MSDS Name: SF-400 SUBFLOOR & CONSTRUCTION ADHESIVE
MSDS Number: 40029
Version Number 2
MSDS Date: SEP-09-2002
Page Number: 5

PROTECTIVE CLOTHING:

Rubber gloves should be worn where skin contact is likely.
Wear impervious clothing and shoes.

EYE PROTECTION:

Chemical goggles or safety glasses should be worn.

HANDLING AND STORAGE PRECAUTIONS:

Keep away from heat, spark and flame.
Keep out of reach of children.
Keep container closed while not in use.
Do not cut or burn recepticals that have contained a
solvent based product. Do not reuse this container.
Use only in a well ventilated area.

N/A=NOT APPLICABLE N/AV=NOT AVAILABLE N/E, N/est=NOT ESTABLISHED

SECTION IX - TRANSPORT INFORMATION:

DOT CLASSIFICATIONS FOR ONE GALLON AND UNDER CONTAINERS

DESCRIPTION: ORM-D, Consumer commodity
CLASS/ UN NO.: none
DOT LABEL: ORM-D (Adhesives)
IMDG class: 3.1
IMDG BOL: Adhesive, 3, UN1133, PG III, LTD QTY

DOT CLASSIFICATIONS for OVER 1 GALLON size CONTAINERS

DESCRIPTION: Adhesive
CLASS: Class 3, Packing group III
DOT LABEL: Flammable Adhesive, UN 1133
IMDG CLASS: 3.1
IMDG BOL: Adhesive, 3, UN1133, PG III

SECTION X - REGULATORY INFORMATION:

SARA TITLE III SECTION 313:

This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right to Know Act of 1986 and of 40 CFR 372:

Ingredient Name	CAS Number	Percent
-----------------	------------	---------

MATERIAL SAFETY DATA SHEET

MSDS Name: SF-400 SUBFLOOR & CONSTRUCTION ADHESIVE

MSDS Number: 40029

Version Number 2

MSDS Date: SEP-09-2002

Page Number: 6

Toluene	108-88-3	5 - 10
---------	----------	--------

n-Hexane	110-54-3	5 - 10
----------	----------	--------

-PROP 65 (TERATOGEN)

WARNING: This product contains a chemical known to the state of California to cause birth defects or other reproductive harm.

Ingredient Name	CAS Number	Percent
-----------------	------------	---------

Toluene	108-88-3	5 - 10
---------	----------	--------

The following ingredients are registered for TSCA 12B

Ingredient Name	CAS Number	Percent
-----------------	------------	---------

n-Hexane	110-54-3	5 - 10
----------	----------	--------

This material fits the EPA Hazard Category definition of Immediate (Acute) and Delayed (Chronic) Health Hazards and Fire Hazard under SARA Sections 311, 312.

Chemical ingredients are listed on the TSCA inventory.

DISCLAIMER:

The information contained herein is based on data available as of the date of preparation of this MSDS and which we believe to be reliable. However, no warranty is expressed or implied regarding the accuracy of the data. We shall not be responsible for the use of this information, or of any product, method, or apparatus mentioned, and the user must make his own investigation to determine the suitability of the information or products for his particular purpose, for the protection of the environment, and the health and safety of the users of this material.